



PRODUCT DATA SHEET

QH8362

Our patented 3 dB 90° Hybrid Couplers provide:

- Superior component performance starting at 3:1 Bandwidth.
- Thicker center boards for high power and increased repeatability.
- Bonded structures which eliminate any air gaps between substrates.
- More sections per bandwidth for better coupling flatness.
- Electrically shorter and physically smaller RF components.

Features:

High Power Wide Bandwidths Small Size Connectorized Drop-In & Surface Mount

Electrical Specifications:

Frequency: 800 - 4200 MHz
Power: 150 W CW
Insertion Loss: 0.55 dB Max.
VSWR: 1.35:1 Max.
Phase Balance: $90^\circ \pm 5^\circ$ Max.
Amplitude Balance: ± 0.5 dB Max.
Isolation: 18 dB Min.

Mechanical Specifications:

Type: Connectorized
Material: Aluminum 6061-T6
Surface Finish: Chem. Film Per MIL-DTL-5541F Type I Class 3 (Yellow Iridite) RoHS Compliant Available
Operating Temperature: -55°C to +75°C
Storage Temperature: -60°C to +85°C
Weight: 2 oz.
Size: 1.55 x 1.58 x 0.47"

Connector Configurations:

Model	Sum Port (J1)	-90°,0° (J2,J3)	Diff. Port (J4)
QH8362-102	SMA	SMA	SMA


Werlatone's breakthrough technology allows us to build our existing line of Broadband 3 dB High Power 90° Hybrid Couplers. Connectorized 3 dB 90° Hybrid Coupler models are available with a choice of connectors. Several of our existing High Power 3 dB 90° RF Couplers are three port designs, wherein the difference port is internally terminated with a high power termination. This eliminates the need for a customer supplied external load for each Hybrid Coupler.



WERLATONE

Model QH8362

90° Hybrids Connectorized




PRODUCT DATA SHEET


QH8362

Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Isolation:



Phase Balance:




Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION
 This document contains proprietary information which is the sole property of Werlatone, Inc.

REVISION HISTORY				
DATE	REV	DESCRIPTION	AUTHOR	CHECKED BY
4/9/2009	-	INITIAL RELEASE	GP	NH
6/6/2013	A	ECN 8214	GP	BW



		UNLESS OTHERWISE SPECIFIED		DWN	GP	DATE	 WERLATONE SINCE 1965	17 Jon Barrett Rd Patterson, NY 12563		
		• INTERPRET DRAWING IN ACCORDANCE WITH MIL-STD-100 • DIMENSIONS UNLESS OTHERWISE SPECIFIED ARE IN INCHES • DIMENSIONS IN PARENTHESES ARE FOR REFERENCE ONLY • DIMENSIONS UNLESS OTHERWISE SPECIFIED ARE IN INCHES • DIMENSIONAL LIMITS APPLY BEFORE PROCESSING		CHK	CS	DATE				
				ENGR	GP	DATE	TITLE			
				APVD	BW	DATE	3dB, 90° Hybrid Coupler			
NEXT ASSY		USED ON		QA		DATE	SIZE	CAGE CODE	DWG NO	REV
							A	28812	20510-500	A
APPLICATION				RLSE		DATE	SCALE	1:1		SHEET 1 OF 1
		THIRD ANGLE PROJECTION 								

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
 Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com