

**PRODUCT DATA SHEET****D5072**

**Werlatone® Mismatch Tolerant®** High Power Broadband RF Combiners and Dividers will operate into High Load VSWR Conditions, for extended periods, without damage. With extensive experience as a supplier to military platforms worldwide **Werlatone®** designs its High Power Broadband Combiners, Power Dividers, and N-Way Combiners for proper operation in the most stringent operating conditions.

**Features:**

High Power      Wide Bandwidths      Small Size      High Isolated      Custom Designs Available

**Electrical Specifications:**

Frequency: 800 - 960 MHz  
Power: 300 W CW  
Insertion Loss: 0.4 dB Max.  
VSWR: 1.30:1 Max.  
Phase Balance:  $\pm 5^\circ$  dB Max.  
Amplitude Balance: 0.2 dB Max.  
Isolation: 20 dB Min.

**Mechanical Specifications:**

Type: Connectorized  
Material: Aluminum 6061-T6  
Surface Finish: Electroless Nickel-ASTM B733 Type IV  
Operating Temperature: -55°C to +75°C  
Storage Temperature: -60°C to +85°C  
Weight: 2.5 lbs.  
Size: 3.0 x 5.0 x 2.0"

**Connector Configurations:**

| Model    | Sum Port (J1) | Input/Output (J2) | Input/Output (J3) |
|----------|---------------|-------------------|-------------------|
| D5072-10 | N Female      | N Female          | N Female          |

**When specified, Werlatone® High Power Combiners and RF Dividers** will tolerate full input failures on adjacent port(s). This insures that remaining transmitter(s) may continue to operate until the amplifier system can be properly shut down for maintenance. Choose your specific connector configuration from a list of options. Additional connector configurations for our High Power RF Combiners/Dividers, Non-Coherent Combiners, and N-Way Combiners are available upon request.