



## PRODUCT DATA SHEET

D5704

**Werlatone® Mismatch Tolerant®** High Power Broadband RF Combiners and Dividers will operate into High Load VSWR Conditions, for extended periods, without damage. With extensive experience as a supplier to military platforms worldwide **Werlatone®** designs its High Power Broadband Combiners, Power Dividers, and N-Way Combiners for proper operation in the most stringent operating conditions.

### Features:

High Power      Wide Bandwidths      Small Size      High Isolation      Custom Designs Available

### Electrical Specifications:

Frequency: 0.1 - 30 MHz  
Power: 1000 W CW  
Insertion Loss: 0.3 dB Max.  
VSWR: 1.30:1 Max.  
Phase Balance:  $\pm 5^\circ$  Max.  
Amplitude Balance: 0.2 dB Max.  
Isolation: 20 dB Min.

### Mechanical Specifications:

Type: Connectorized  
Material: Aluminum 6061-T6  
Surface Finish: Chem. Film Per MIL-DTL-5541F Type I Class 3 (Yellow Iridite) RoHS Compliant Available  
Operating Temperature: -55°C to +75°C  
Storage Temperature: -60°C to +85°C  
Size: 7.0 x 5.5 x 2.25"

### Connector Configurations:

| Model    | Sum Port (J5) | Input/Output (J1-J4) |
|----------|---------------|----------------------|
| D5704-10 | N Female      | N Female             |
| D5704-13 | N Female      | BNC                  |
| D5704-20 | 7/16 Female   | N Female             |
| D5704-50 | C Female      | N Female             |

**When specified, Werlatone® High Power Combiners and RF Dividers** will tolerate full input failures on adjacent port(s). This insures that remaining transmitter(s) may continue to operate until the amplifier system can be properly shut down for maintenance. Choose your specific connector configuration from a list of options. Additional connector configurations for our High Power RF Combiners/Dividers, Non-Coherent Combiners, and N-Way Combiners are available upon request.




## PRODUCT DATA SHEET


D5704

### Performance Data (Specifications subject to change without notice):


Insertion Loss:




VSWR:




Isolation:



Phase Balance:



| DATE | SYM | REVISION RECORD | AUTH | DR | CK |
|------|-----|-----------------|------|----|----|
| 9/01 |     | REV A ECN 2067  | BW   |    |    |
| 3/02 |     | REV B ECN 3076  | RH   |    |    |
|      |     |                 |      |    |    |
|      |     |                 |      |    |    |



THIS DRAWING CONTAINS INFORMATION  
PROPRIETARY TO WERLATONE INC. AND  
MAY NOT BE USED OR COPIED WITHOUT  
THE WRITTEN CONSENT OF WERLATONE INC.

|                                |                  |                             |                |
|--------------------------------|------------------|-----------------------------|----------------|
| TOLERANCE<br>(EXCEPT AS NOTED) | WERLATONE INC.   |                             |                |
| XX +/- .015<br>XXX +/- .005    | SCALE            | DRAWN BY MW                 | APPROVED BY CS |
|                                | TITLE<br>OUTLINE |                             |                |
|                                | DATE<br>7/3/01   | DRAWING NUMBER<br>10745-501 |                |

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.  
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com