

PRODUCT DATA SHEET

D5876

Werlatone® Mismatch Tolerant® High Power Broadband RF Combiners and Dividers will operate into High Load VSWR Conditions, for extended periods, without damage. With extensive experience as a supplier to military platforms worldwide **Werlatone®** designs its High Power Broadband Combiners, Power Dividers, and N-Way Combiners for proper operation in the most stringent operating conditions.

Features:

High Power Wide Bandwidths Small Size Custom Designs Available

Electrical Specifications:

Frequency: 150 - 1000 MHz
Power: 350 W CW
Insertion Loss: 0.65 dB Max.
VSWR: 1.30:1 Max.
Phase Balance: $\pm 3^\circ$ Max.
Amplitude Balance: 0.25 dB Max.
Isolation: Non-Isolated

Mechanical Specifications:

Type: Connectorized
Material: Aluminum 6061-T6
Surface Finish: Chem. Film Per MIL-DTL-5541F Type I Class 3 (Yellow Iridite) RoHS Compliant Available
Operating Temperature: -55°C to +75°C
Storage Temperature: -60°C to +85°C
Size: 8.38 x 7.55 x 1.5"

Connector Configurations:

Model	Sum Port (J1)	Input/Output (J2-J4)
D5876-10	N Female	N Female
D5876-10B	N Female	N Female

The D5876-10B has a Black Epoxy Paint/White Epoxy Lettering Finish


When specified, Werlatone® High Power Combiners and RF Dividers will tolerate full input failures on adjacent port(s). This insures that remaining transmitter(s) may continue to operate until the amplifier system can be properly shut down for maintenance. Choose your specific connector configuration from a list of options. Additional connector configurations for our High Power RF Combiners/Dividers, Non-Coherent Combiners, and N-Way Combiners are available upon request.



WERLATONE

Model D5876

Combiners In-Phase Connectorized




PRODUCT DATA SHEET


D5876

Performance Data (Specifications subject to change without notice):

Insertion Loss:




VSWR:



For In-Building Applications:



Phase Balance:



Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

