



PRODUCT DATA SHEET

WPM11490

Instantaneous & Simultaneous

- Local and/or Remote Monitoring
- Forward Power Reading/Monitoring (Watts or dBm)
- Reverse Power Reading/Monitoring (Watts or dBm)
- VSWR Readings (Watts, Return Loss, Rho)

VSWR Alarm

- Customer can set up audio/visual alarm via relay contacts.
- Signal sent to closed loop.

Temperature Monitoring (with alarm)

- One sensor, internal measurement, within Power Meter.
- One sensor, external measurement, to be placed by customer.

General Purpose Inputs (6 ea) Multiple Use

- Track switch closures (assign to interlock group).
- Trigger alarm relay (sends email alert).
- RF presence status/alarm (saftey feature).
- Alarm, activated switch.

Accessories:

- Single Channel and Multi-Channel Displays
- RF Digital Dashboard Spreadsheet Software, (Simultaneously Monitor Outputs of 30+ Power Meters)
- PC Based Graphical User Interface Windows XP/7/8/10 Compatible

Accuracy:

- $\pm 2\%$ to Customer Calibration Standard, at preselected frequencies.
- $\pm 5\%$ over a Multi-Octave Bandwidth
- Werlatone Calibration Traceable to (NIST) National Institute of Standards and Technology

Power:

- AC Power Adapter (100/240 50-60 Hertz V AC)
- POE (Passive Over Ethernet, Optional POE Injector Kit Available)
- Via RS485 (Via Single Channel or Multi-Channel Displays)

Interface (Via):

- TCP/IP - SNMP and Browser Interface via Local Area Network
- RS232, Serial
- RS485 - Form Addressable Serial Network
- User ID and Password Protected for Access and Control
- Multiple units can be Networked and Simultaneously Monitored On-Site or Remotely (TCP/IP/SNMP/Serial)

RoHS Compliant Design Available
Custom Connector Configurations Available

Electrical Specifications:

Frequency: 10 - 127 MHz
Power: 20,000 W CW

Calibrated to Exact Frequencies:

12.882 MHz 13.56 MHz 14.238 MHz
57.0 MHz 60.0 MHz 63.00 MHz
127.00 MHz

Mechanical Specifications:




Type: Connectorized
Operating Temperature: -55°C to +75°C
Storage Temperature: -60°C to +85°C

Connector Configurations:

Model	Input(J1)	Output(J2)
WPM11490-502	SQS Female	SQS Female
WPM11490-7502	SQS Male	SQS Female
WPM11490-QC-2	QC Block	QC Block

RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION
This document contains proprietary information which is the sole property of Werlatone, Inc.

REVISION HISTORY			
REV.	REVISION RECORD	DATE	APPROVED
-	INITIAL RELEASE	2/12/2018	CS



4X Ø .11 [2.7] .25 [6.4]
6-32 UNC - 2B .28 [7.0]
FAR SIDE

UNLESS OTHERWISE SPECIFIED		OWN	PLP	DATE	2/9/2018
• INTERPRET DRAWING IN ACCORDANCE WITH ASME Y14.5-2009		CHK	CS	DATE	2/9/2018
• DIMENSIONS ARE IN INCHES (MM)		ENGR		DATE	
• DIMENSIONAL LIMITS APPLY BEFORE FINISHES		INFR		DATE	
• TOLERANCES:		QA		DATE	
ANGLES: 1:2		RELSE		DATE	
2 PL ± .005 (1:3)					
2 PL ± .015 (1:4)					
• REMOVE ALL BURRS AND SHARP EDGES 0.01 MAX					
• CONCENTRICITY MACHINED DIA. AND FOM					
• MACHINE TOOL IDENTIFICATION AND MARK					
THIRD ANGLE PROJECTION					
WPM11416					
NEXT ASSY USED ON					
APPLICATION					
TITLE					
OUTLINE					
SIZE					
B 28812					
CAGE CODE					
21583-500					
DWG NO					
REV					
-					
SCALE					
1:2					
SHEET 1 OF 1					

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com