

PRODUCT DATA SHEET

C6721

4-Port Dual Directional Coupler employs two, 3-Port Uni-Directional Couplers, internally connected, in tandem, providing measurement of both forward and reverse power. Ideal for simultaneously monitoring a system's forward and reverse power and for reflectometer measurements. Unlike the Bi-Directional Coupler, the directivity of the Dual Directional Coupler is unaffected by the loads on the coupled ports.

Features:

High Power Wide Bandwidths Small Size Flat Coupling Custom Designs Available

Electrical Specifications:

Frequency: 800 - 3000 MHz
Power: 400 W CW
Coupling: 40 ± 1.0 dB Max.
Insertion Loss: 0.2 dB Max.
Flatness: ± 0.75 dB Max.
VSWR (ML): 1.30:1 Max.
Directivity: 20 dB Min.

Mechanical Specifications:

Type: Connectorized
Material: Aluminum 6061-T6
Surface Finish: Chem. Film Per MIL-DTL-5541F
Type I Class 3 (Yellow Iridite)
RoHS Compliant Available
Operating Temperature: -55°C to +75°C
Storage Temperature: -60°C to +85°C
Humidity: 95% Non-Condensing
Size: 3.0 x 3.0 x 1.09"

Connector Configurations:

Model	Input (J1)	Output (J2)	Fwd (J3)	Rev (J4)
C6721-10	N Female	N Female	N Female	N Female
C6721-12	N Female	N Female	SMA	SMA
C6721-13	N Female	N Female	BNC	BNC
C6721-20*	7/16 Female	7/16 Female	7/16 Female	7/16 Female
C6721-22*	7/16 Female	7/16 Female	SMA	SMA
C6721-23*	7/16 Female	7/16 Female	BNC	BNC
C6721-102	SMA	SMA	SMA	SMA
C6721-627*	7/16 Female	7/16 Female	N Female	N Female
C6721-712	N Male	N Female	SMA	SMA
C6721-714	N Male	N Female	N Female	N Female
C6721-727*	7/16 Male	7/16 Female	N Female	N Female
C6721-728*	7/16 Male	7/16 Female	SMA	SMA


*Starred options are 3.0 x 3.0 x 1.59"



WERLATONE

Model C6721

Connectorized Directional Couplers




PRODUCT DATA SHEET


C6721

Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Insertion Loss:




Directivity:



Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION
This document contains proprietary information which is the sole property of Werlatone, Inc.



REVISION HISTORY			
REV.	REVISION RECORD	DATE	APPROVED
A	ECN 9696	11/27/18	RB

NOTES: UNLESS OTHERWISE SPECIFIED

- MATERIAL: ALUMINUM 6061-T6**
- FINISH: CHEM FILM PER MIL-DTL_5541F TYPE I CLASS 3 (YELLOW IRIDITE)**

		UNLESS OTHERWISE SPECIFIED		DWGN	DATE	17 Jon Barrett Rd	
		• INTERPRET DRAWING JAW MIL-STD-100		RH	7/5/2001	Patterson, NY 12563	
		• DIMENSIONING PER ASME Y14.5M-2009		CHK	DATE	WERLATONE® SINCE 1965	
		• PARENTHESES FOR REF ONLY		ENGR	DATE		
		• DIMENSIONS ARE IN INCHES		MJ	7/5/2001	TITLE OUTLINE	
		• DIMENSIONAL LIMITS APPLY BEFORE PROCESSES		MPGR	DATE		
		• TOLERANCES:		QA	DATE	B CAGE CODE DWG NO 10379-505	
		• ANGLES ± 2°		RLSE	DATE		
		• 3 PL ± .005 [1.3]				SCALE 1:1	
		• 2 PL ± .015 [3.8]					
		• REMOVE ALL BURRS AND SHARP EDGES R.01 MAX				REV A	
		• CONCENTRICITY MACHINED DIA: .002 FIM					
		• MACHINE TOOL MISMATCH .003 MAX					
NEXT ASSY USED ON		THIRD ANGLE PROJECTION 					
APPLICATION							
				SHEET 1 OF 1			

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com