



## PRODUCT DATA SHEET

C9639

**4-Port Bi-Directional Coupler:** Similar to the 3-Port Uni-Directional Coupler, except that both ends of the coupled line serve as coupled ports. Convenient for simultaneously monitoring both forward and reverse power. The directivity of this coupler design is, however, dependent upon well matched 50 Ohm loads on the coupled ports.

### Features:

High Power      Wide Bandwidths      Small Size      Flat Coupling      Custom Designs Available

### Electrical Specifications:

Frequency: 2500 - 6000 MHz  
Power: 100 W CW  
Coupling:  $20 \pm 1.0$  dB Max.  
Insertion Loss: 0.4 dB Max.  
Flatness:  $\pm 1.0$  dB Max.  
VSWR (ML): 1.25:1 Max.  
Directivity: 18 dB Min.

### Mechanical Specifications:

Type: Connectorized  
Material: Aluminum 6061-T6  
Surface Finish: Chem. Film Per MIL-DTL-5541F  
Type I Class 3 (Yellow Iridite)  
RoHS Compliant Available  
Operating Temperature: -55°C to +75°C  
Storage Temperature: -60°C to +85°C  
Humidity: 95% Non-Condensing  
Size: 1.1 x 0.75 x 0.48"  
Weight: 0.9 ounces / 26 grams

### Connector Configurations:

| Model     | Input (J1) | Output (J2) | Fwd (J3) | Rev (J4) |
|-----------|------------|-------------|----------|----------|
| C9639-102 | SMA        | SMA         | SMA      | SMA      |

**Werlatone®** Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition. Our multi-octave Directional Couplers maintain exceptional coupling flatness, directivity, VSWR, and insertion loss.



# WERLATONE

Model C9639

Connectorized Directional Couplers




## PRODUCT DATA SHEET


C9639

### Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Insertion Loss:



Directivity:



**Restriction on use, duplication, or disclosure of proprietary information.** This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com



**RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION**

This document contains proprietary information which is the sole property of Werlatone, Inc.

| REVISION HISTORY |                 |           |          |
|------------------|-----------------|-----------|----------|
| REV.             | REVISION RECORD | DATE      | APPROVED |
| A                | ECN 9696        | 8/21/2019 | RB       |

**NOTES: UNLESS OTHERWISE SPECIFIED**

- MATERIAL: ALUMINUM 6061-T6**
- FINISH: CHEM FILM PER MIL-DTL-5541F TYPE I CLASS 3 (YELLOW IRIDITE)**
- CONNECTORS: J1-J4: SMA FEMALE**



|                   |  |                                           |  |                        |           |                                                                                                            |  |                                          |  |
|-------------------|--|-------------------------------------------|--|------------------------|-----------|------------------------------------------------------------------------------------------------------------|--|------------------------------------------|--|
|                   |  | UNLESS OTHERWISE SPECIFIED                |  | OWN                    | DATE      |  WERLATONE SINCE 1965 |  | 17 Jon Barrett Rd<br>Patterson, NY 12563 |  |
|                   |  | INTERPRET DRAWING IAW MIL-STD-100         |  | SD                     | 8/21/2019 | TITLE                                                                                                      |  | <h1>OUTLINE</h1>                         |  |
|                   |  | DIMENSIONING PER ASME Y14.5M-2009         |  | CHK                    | DATE      |                                                                                                            |  |                                          |  |
|                   |  | PARENTHESES FOR REF ONLY                  |  | CS                     | 8/21/2019 | ENGR                                                                                                       |  | SIZE CAGE CODE DWG NO                    |  |
|                   |  | DIMENSIONS ARE IN INCHES                  |  | ENGR                   | DATE      |                                                                                                            |  |                                          |  |
|                   |  | DIMENSIONAL LIMITS APPLY BEFORE PROCESSES |  | INFR                   | DATE      | QA                                                                                                         |  | SCALE                                    |  |
|                   |  | TOLERANCES:                               |  | QA                     | DATE      |                                                                                                            |  |                                          |  |
|                   |  | ANGLES ± 2°                               |  | RLSE                   | DATE      | 20643-500                                                                                                  |  | REV<br>A                                 |  |
|                   |  | 3 PL ± .005 [13]                          |  |                        |           |                                                                                                            |  |                                          |  |
|                   |  | 2 PL ± .015 [38]                          |  |                        |           | B 2:1                                                                                                      |  | SHEET 1 OF 1                             |  |
|                   |  | REMOVE ALL BURRS AND SHARP EDGES R.01 MAX |  |                        |           |                                                                                                            |  |                                          |  |
|                   |  | CONCENTRICITY MACHINED DIA. .002 FIM      |  |                        |           |                                                                                                            |  |                                          |  |
|                   |  | MACHINE TOOL MISMATCH .003 MAX            |  |                        |           |                                                                                                            |  |                                          |  |
| NEXT ASSY USED ON |  | APPLICATION                               |  | THIRD ANGLE PROJECTION |           |                                                                                                            |  |                                          |  |

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.  
 Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com